Mathematical Modelling of Work of Modern Friction-Polymer Shock Absorbers and Determining the Dynamical Force during the Impact

Hristijan Mickoski, Ivan Mickoski and Petar Simonovski

Faculty of Mechanical Engineering, University of Skopje, Skopje 1000, Macedonia

Abstract: Shock absorbers are main elements into construction of train wagons that secure protection from longitudinal forces which appear during transitional regimes of movement. Besides, development of new constructive solutions for shock absorbers is quite popular development of their working mathematical models. This paper presents modern shock absorber with elastic block made from polymer elements that increase quantity of absorbed energy. This is achieved by increasing the stiffness characteristic of polymer elastic block. The construction is relatively simple and technology used to create the construction is with more or less low price. If there is not enough elastic stiffness of the polymer block, there is a possibility for not meeting the UIC (International Union of Railways) norms for absorbed energy. Therefore, according to the mentioned characteristic, shock absorbers are divided into three groups. The mathematical model presented in this paper allows calculating the necessary elastic characteristic of the polymer block for a short time. Differential equation of movement of the shock absorber elements is presented in this paper. Force change of polymer block for various impact velocities participates in the differential equation of movement where initial velocity V_0 and the current meaning of the velocity $\dot{x}$ are taken into consideration. The presented equation is solved by using program language MATLAB/Simulink by developing a simulation model.

Key words: Shock absorber, mathematical modelling, MATLAB/Simulink, simulation, dynamical force.

1. Introduction

Rail freight transport occupies an important role in the transport system of each country in the world. Increasing the transport of goods in recent years respectively led to increased weight of train wagons and speed collision during their manoeuvrability and during forming the compositions of arranged stations. All this significantly increased the level of activity of the longitudinal forces acting on the train wagons as a result of load occurrence of massive repairs which appreciably reduce revenue from transportation of goods.

The main element for reducing the level of longitudinal forces in the operation of railway vehicles, especially freight vehicles, is shock absorbers that are

embedded on the front of each train wagon. Therefore, for such a role in the recent years, new constructive solutions have been developed, where absorption capacity-efficiency of longitudinal forces takes a package made by polymeric materials which are embedded in the shock absorber.

The influence of the speed impact on shock absorber is a factor studied for a long time by many authors, but it remains an unexplored issue regarding the influence of the speed impact on the characteristics of modern polymer elements.

According to the experimental data, a mathematical model was created for changing the force F acting on the retaining polymer package which takes into account the impact of initial speed V_0 as well as the change of the current speed $\dot{x}$. The error of this resulting force does not exceed 6% in terms of maximum 1% compared to the maximum of Ref. [1].

Corresponding author: Ivan Mickoski, Ph.D., professor, research fields: mechanics/mechatronics and railway vehicles. E-mail: ivan.mickoski@mf.edu.mk.

Strict UIC (International Union of Railways) requirements for towing shock absorber devices for freight wagons and locomotives require forces smaller than 2.0 MN in order to achieve energy absorber capacity not less than 70 kJ and the full force less than 3.0 MN to achieve energy capacity not less than 90 kJ. Then, when there is insufficient stiffness of embedded polymer block, it will not achieve the required energy capacity if the rigidity is increased, there will be increase of the pressing forces. Therefore, determination of stiffness characteristic of embedded polymer block is an important and responsible issue.

This paper presents the calculation of the dynamic force acting on the polymer block during collision. Movement of the swept elements of shock absorber is expressed with differential equation where dynamical force is taken, from where the stiffness characteristic of polymer block that can satisfy the above requirements can be accurately determined. Principle scheme of elastic-frictional absorption device (shock absorber) with package of polymer elements is given in Figs. 1 and 2. A complete shock absorber is given in Fig. 3.

2. Mathematical Modelling

A need to develop mathematical modelling of absorption devices arises due to the above-mentioned requirements, and it would further be used to determine

the optimal stiffness characteristics of the embedded polymer block and reduce their cost for obtaining. The differential equation of motion of the elements of the system swept parts (Fig. 1) has the following form:

$$\ddot{x} = g - \frac{\psi \cdot F}{M} \quad (1)$$

where:

x is displacement of cone pressure part;

$\dot{x}$ is velocity of cone pressure part;

$\ddot{x}$ is acceleration of cone pressure part;

ψ is coefficient of transmission, showing for how much pressure force of the shock absorber P oversized the pressure force of the embedded polymer block F . At our case, $\psi = 5$ is taken. Calculation of ψ is given in Refs. [2, 3]. Following equations are given in Refs. [4-6]:

$$F = a(v_0 - \dot{x}) - b \quad (2)$$

$$a = 101.2x^3 - 30.66x^2 + 3.98x - 0.062$$

$$b = 0.0083e^{24x}$$

Force F expressed in kN has nonlinear characteristic and up to now was estimated experimentally. M is the mass of the moving system. Force P depends on system velocity and system position, which can be calculated from known estimation in which angles of cone metal element participate and friction coefficient between

Fig. 1 Principle scheme of elastic-frictional absorption device.

Fig. 2 Principle scheme of elastic-frictional absorption device (shock absorber) with package of polymer elements.

them, so force P can be estimated with Eq. (3) bellow. Nevertheless, up to now, same force was estimated experimentally.

Force F can be expressed with equation:

$$P = \frac{d(M\dot{x})}{dt} \quad (3)$$

with replacing the expression $dt = \frac{dx}{\dot{x}}$ into Eq. (3), we will have first order differential equation:

$$Mx\dot{x} = Pdx \quad (4)$$

$$P = M \cdot g - \psi \cdot F \quad (5)$$

With replacing Eq. (5) into Eq. (4), we will have differential equation of motion of the elements of the system swept parts Eq.(1).

3. MATLAB/Simulink Modelling

For solving Eqs. (1) and (2), imitational models are developed by using program package MATLAB/Simulink. Fig. 4 presents a block diagram of imitational model for solving dynamical force F given with Eq. (2). Fig. 5 presents a block diagram of imitational model for estimation of displacement and velocity of moving system from shock absorber (Eq. (1)).

Fig. 3 Complete shock absorber

Fig. 4 Block diagram of imitational model for solving dynamical force F .

Fig. 5 Block diagram of imitational model for estimation of displacement and velocity.

Fig. 6 Changing of dynamical force F , estimated from imitational model from Fig. 4.

Fig. 7 Displacement and velocity obtained with simulation of imitational model shown in Fig. 6.

4. Conclusions

Based on the mathematical model for changing the dynamic force F (Fig. 6) acting on polymer embedded package that takes into calculation influence of initial speed of the impact v_0 , as well as change of the current speed $\dot{x}$, imitational model for force calculation is developed, from where it can be accurately determined stiffness characteristic of the polymer block that can satisfy the requirements of UIC without doing any further tests, which are very expensive from a economical point of view.

Using the data obtained for dynamic force and change of the current speed, we are recommending for future work optimization of polymeric embedded package and satisfying the energy capacity of the absorber in accordance with UIC standards.

An imitational model for calculation of displacement and velocity of moving system from shock absorber during period of collision (collision of the train wagons) is developed, and the results are given in Fig. 7.

Future optimization of the slopes of pressure elements (Fig. 1) can be very important component for more precise calculation of the influence of the self exciting vibrations of the buffer during collision of the

wagons.

References

- [1] Nikolskii, L. N. 1986. *Railway Vehicles Shock-Absorbers*. Moscow: Машиностроение (Machinery Construction). (in Russian)
- [2] Mjamlin, S. V., Naumenko, N. E., and Nikitcenko, A. A. 2008. "Designing Mathematical Model for Friction Polymer Shock Absorber." *Visnik Dnipropetrovs'kogo Nacional'nogo Universitetu Zalizničnogo Transportu (Bulletin of Dnipropetrovsk National University of Railway Transport)* 24: 25-33. (in Russian)
- [3] Manashkin, L., Myamlin, S., and Prikhodko, V. 2009. "Oscillation Dampers and Shock Absorbers in Railway Vehicles (Mathematical Models)." Monograph, Ministry of Transport and Communication of Ukraine, Dnepropetrovsk/Ukraine.
- [4] Zirov, P. D. 2011. "Modeling of Exploitation Factors with Influence on Effective Work of Modern Shock Absorbers." In *Proceedings of III International Scientific Practice Conference*, 24-5. (in Russian)
- [5] Zirov, P. D. 2012. "Influence Evaluation of Exploitation Factors for Work Efficiency of the Adsorption Devices at Shock-Absorbers." Ph.D. thesis, Bryansk State Technical University.
- [6] Zirov, P. D. 2012. "Development of Mathematical Model and Characteristics Calculation of Shock-Absorber Adsorption Device with Polymer Elements on Different Temperatures of Working Environment." *Scientific and Technical Journal "Vestnik BSTU"* 4: 9-11. (in Russian)