A Geological Classification of Rock Mass Quality and Blast Ability for Widely Spaced Formations

Maria Chatziangelou and Basile Christaras

Department of Geology, Aristotle University of Thessaloniki, Thessaloniki 54631, Greece

Abstract: Success in the excavation of geological formations is commonly known as being very important in asserting stability. Furthermore, when the subjected geological formation is rocky and the use of explosives is required, the demands of successful blasting are multiplied. The present paper proposes a classification system, named: BQS (blast ability quality system), for rock masses with widely spaced discontinuities (spacing longer than 1 m). It is obvious that rock quality is one of the main characteristics which define the blast ability of a rock. The BQS can be an easy and widely-used tool as it is a quick evaluator for blast ability and rock mass quality at one time. Taking into consideration the research calculations and the parameters of BQS, what has been at question in this paper is the effect of blast ability in a geological formation with widely spaced discontinuities.

Key words: Geological classification, blast ability, rock mass, quality, methodology.

1. Introduction

The several geological formations, which are affected by numerous stages of disintegration in varying stress conditions, may act in a different manner under specified blast design, explosive characteristics and specified legislative constraints depending on the site specifics.

The present paper improves “Blastability Quality System” [1] by combining the quality with the blast ability of a rock mass [2], which can be easily used in situ, in order to estimate, easily, the explosion results [3] in relation to the excavation methods. The geological provision of explosion results and the ability of engineering geologists or engineers to choose quickly, the most applicable way of blasting, minimize, in the same time, the percentage of instability problems.

2. Theory

2.1 Rock Mass Quality Using RMR (Rock Mass Rating) Classification System

RMR classification system [4], is based on

Corresponding author: Chatziangelou Maria, research collaborator, research fields: engineering geology and tunneling.

mechanical and structural characteristics of rock mass. The RMR index is calculated;

$$\text{RMR} = A1 + A2 + A3 + A4 + A5 + B$$

where, A1 = rating for the uniaxial compressive strength of the rock material, A2 = rating for the drill core quality RQD, A3 = ratings for the spacing of joints, A4 = ratings for the condition of joints, A5 = ratings for the ground water conditions, and B = ratings for the orientation of joints.

From the value of RMR in the actual excavation, the rock support can be estimated. RMR can be used to crudely estimate the deformation modulus of rock masses, too. Bieniawski [4] strongly emphasizes that a great deal of judgment is used in the application of a rock mass classification system in support design [5].

In the RMR system, there is no input parameter for rock stresses, but stresses up to 25 MPa which are included in the estimated RMR value as the strength for intact rock material (point load strength index and uniaxial compressive strength) is used. According to Palmstrom [6] “overstressing (rock bursting and squeezing)” is not included. Whether of how faults and weakness zones are included, is unclear. No special parameter for such features is used, but some of the

parameters included in the system may represent conditions in faults, though the often complicated structure and composition in these features are generally difficult to characterize or classify. Therefore, it is probable that RMR does not work well for many faults and weak zones. Swelling rock is not included in the RMR system.

2.2 Geological Strength Index

The GSI (geological strength index) [7, 8] relates to the overall rock mass quality. It is based on an assessment of the lithology, structure and condition of discontinuous surfaces in the geological foundations and is estimated through visual examination of rock mass exposed in crops, surface excavations such as road cuts, tunnel faces or borehole cores. It utilizes two fundamental parameters of the geological process (block size of the mass and discontinuities characteristics); hence it takes into consideration the main geological constraints that govern a formation. In addition, the index is simple to assess in the field [9].

According to Palmstrom [10], block size and discontinuity spacing can be measured by means of the Volumetric Joint Count J_v , or by means of block volume, V_b . Sommez and Ulusay [11] quantified block size in the GSI chart by the SR (structure rating) coefficient that is related to the J_v coefficient. Cai et al. [12] have presented a quantifier using the mean of discontinuity spacing S of the main block volume V_b . The structure was quantified by joint spacing in order to calculate the block volume, and the joint surface condition was quantified by a joint condition factor. The GSI is therefore built on the linkage between descriptive geological terms and measurable earth field parameters such as joint spacing or roughness. So, based on the above information, GSI uses the description of rock mass structure—as laminated and sheared, disintegrated, blocky and disturbed, very blocky, blocky and intact of massive—referring to the block size and discontinuity space and the description of surface conditions—or as very poor, poor, fair, good

and very good—referring to the joint surface conditions.

The rock mass type is a controlling factor in the assessment of the earth excavation method, as it is closely related to the number of discontinuity sets and reflects the rock mass structure. The GSI in its original form, was not scale dependent, thus the block size is not directly related to the rock mass type. Nevertheless, each rock type has a broad correlation to the rock block size, i.e., a rock mass which is characterized as “blocky” has bigger blocks than a rock mass which is characterized as “very blocky” or “disintegrated”, that is, made up of very small rock fragments. The concept of block volume is not applicable on schist, as the spacing of the schistosity planes equates to the discontinuity planes. For this reason, the present classification for the assessment of excavation ability is based on the original GSI charts (version 2000). Hoek and Karzulovic [8] suggested a range of GSI values for different excavation methods. They proposed that rock masses can be dug up when GSI is estimated to be about 40 and the rock mass strength is about 1 MPa, while ripping can be used when GSI is estimated between 40 and 60 and rock mass strength is about 10 MPa. Blasting was the only effective excavation method when GSI is greater than 60 and rock mass strength is more than 15 MPa.

2.3 Blastability Index Concerning Rock Mass Classification Systems

The factors that influence blasting results fall into two groups. The first group concerns the intact rock properties, which includes strength, hardness, elasticity, deformability, density of rock, etc. The qualities depend on texture, internal bonds, composition and distribution of minerals in the geological foundation. The second group concerns the discontinuity structure, which includes the orientation, spacing, the extent of discontinuities, and the in-situ block sizes created by a range of long-term geological processes.

The coefficient of BI (blastability index) is a

quantitative measure of the blastability of a rock mass. It will be most advantageous for the coefficient BI to be determined before blasting in order to help with the blast design of an excavation. Without any realistic chance in the short term of a practical analytical solution to define the value of the BI for a given rock mass as a function of material properties, the development of a comprehensive assessment system for quantifying the blastability of geological masses would appear to have great potential [13].

BI is used for the description of the ease of blasting and it is also related to rock fragmentation [14] or power factor. When the BI is lower than 8, the ease of blasting is described as “very difficult”. When the BI range is between 8 and 13, the ease of blasting is described as “difficult”. When the BI range is between 13 and 20, the ease of blasting is described as “moderate”. When the BI range is between 20 and 40, the ease of blasting is described as “easy”. When the BI is higher than 40, the ease of blasting is described as “very easy”. This differentiation in description has an immediate effect on excavation cost which always depends on factors like explosion, vibration, disintegration, powder creation etc. [15].

In our study, the BI is to be calculated by the following formula which is proposed by Lilly [16], based on rock mass description, joint density and orientation, specific gravity and hardness:

$$BI = 0.5 \times (RMD + JPS + JPO + SGI + H) \quad (1)$$

where,

BI = blastability index;

RMD (rock mass description) = i) 10, for powdery/friable rock mass, ii) 20, for blocky rock mass, iii) 50, for totally massive rockmass;

JPS (joint plan spacing) = i) 10, for closely spaced discontinuities (< 0.1 m), ii) 20, for intermediate spaced discontinuities (0.1-1 m), iii) 50, for widely spaced discontinuities (> 1 m);

JPO (joint plane orientation) = i) 10, for horizontal, ii) 20, for dip out of the face, iii) 30, for strike normal to face, iv) 40, for dip into face;

SGI = specific gravity influence = $25 \times \text{specific gravity of rock (t/m}^3) - 50$;

H = hardness in mho scale between 1 and 10.

The fact that BI, as it is calculated by Lilly' formula, is based on rock mass description, joint plan spacing and joint plane orientation, and the fact that RMR system is based on the same parameters; geological formation description, joint density and orientation, gave the idea of blastability estimation using classification systems.

3. Results

3.1 Combining Blastability with the Rock Mass Quality

The disturbed, seamy and very blocky rock mass, folded with angular blocks formed by many intersecting discontinuity sets with bedding planes or schistosity, in addition to interlocked, partially disturbed mass with multi-faceted angular blocks formed by four or more joint sets, which are described by the middle part of GSI diagram, has been divided into ten parts: I, J, K, L, M, N, O, P, Q, R. The well interlocked undisturbed blocky rock mass, which consists of cubical blocks formed by three intersecting discontinuity sets, which is described by the above part of GSI diagram, has been divided into five parts: S, T, U, V and W. The intact rock specimens of massive in situ rock with few widely spaced discontinuities, which is described by the upper part of GSI diagram, has been divided into three parts: X, Y, Z (Fig. 1).

Taking into consideration the parameters of Blastability Index $BI = 0.5 \times (RMD + JPS + JPO + SGI + H)$ [11], the BI was calculated for every possible combination of these parameters. This means that RMD was equal to 20 for blocky rock mass and 50 for totally massive rock mass. As the present study concerns widely spaced discontinuities, JPS (joint plan spacing) was equal to 50 for widely spaced. JPO (joint plane orientation) was equal to 10 for horizontal discontinuities, 20 for declined discontinuities where the excavation drives against dip direction, 30 for declined discontinuities with strike parallel to face, 40

Fig. 1 GSI diagram.

for declined discontinuities where the excavation drives with dip direction and SGI (specific gravity influence) was calculated using specific gravity of rocks (t/m^3) from 1-3 (Table 1). And 1,600 different rock mass combinations were estimated (Table 2).

The parameters of the BI calculation are also presented on the Table 2, numbering the rock mass types from 1 to 1,600. At next stage, we regrouped the above rock structures referring to RMR range and GSI parts, taking into consideration rock mass hardness and discontinuities orientation. The range of BI was also calculated (Tables 3-6). GSI range was calculated for every rock mass type with a specific RMR on Tables 4 and 5. The rock structures are numbered from 1 to 1,600 and they were banded together according to RMR range, too. On the same tables GSI parts are equivalent to RMR range. On the Tables 4-6 BI for these grouped rock structures appears in addition to GSI parts. On the same tables RMR range is equivalent to GSI parts.

Finally, a useful diagram of composite rock mass quality and range of the BI aroused from the above estimations (Fig. 2). According to the diagram, the rock mass may consist of horizontal or gradient discontinuities. The gradient discontinuities may have strike perpendicular to tunnel axis or strike parallel to tunnel axis.

In case the rock mass only consists of horizontal discontinuities, the blastability index was calculated between 24 and 54 for disintegrated rock mass and between 29 and 57 for blocky rock mass. According to blasting characterization as it is described on chapter 2.3, blasting is characterized as easy and very easy.

In case of a massive rock mass with horizontal discontinuities, BI was calculated between 44 and 72 and blasting is characterized as very easy.

In case the rock mass consists of inclined discontinuities and the strike of formation is parallel to tunnel axis, the BI was calculated between 31 and 62 for disintegrated rock mass and between 39 and 67 for blocky rock mass. According to blasting

characterizations as it is described on chapter 2.3, blasting is characterized as easy and very easy.

In case of intact and massive rock mass with inclined discontinuities where the strike of formation is parallel to tunnel axis, BI was calculated between 54 and 82 and blasting is characterized as very easy.

In case the rock mass consists of gradient discontinuities and the strike of formation is perpendicular to excavation axis when excavation drives against dip direction, the BI was calculated between 24 and 61 for disintegrated rock mass and between 31 and 62 for blocky rock mass. According to blasting characterization as it is described on chapter 2.3, blasting is characterized as easy to very easy.

In case of intact and massive rock mass with gradient discontinuities where the strike of formation is perpendicular to excavation axis when excavation drives against dip direction, the BI was calculated between 49 and 77. According to blasting characterization as it is described on chapter 2.3, blasting is characterized as very easy.

Table 1 SGI (specific gravity influence).

SGI	
$25 \times \text{specific gravity of rock} (\text{t/m}^3) - 50$	Specific gravity of rock (t/m^3)
-22.5	1.1
-20	1.2
-17.5	1.3
-15	1.4
-12.5	1.5
-10	1.6
-7.5	1.7
-5	1.8
-2.5	1.9
0	2
2.5	2.1
5	2.2
7.5	2.3
10	2.4
12.5	2.5
15	2.6
17.5	2.7
20	2.8
22.5	2.9
25	3

Table 2a BI calculations for widely spaced discontinuities.

α/α	RMD	JPS	JPO
001-20	20	50	10
21-40	20	50	10
41-60	20	50	10
61-80	20	50	10
81-100	20	50	10
101-120	20	50	10
121-140	20	50	10
141-160	20	50	10
161-180	20	50	10
181-200	20	50	10
201-220	20	50	20
221-240	20	50	20
241-260	20	50	20
261-280	20	50	20
281-300	20	50	20
301-320	20	50	20
321-340	20	50	20
341-360	20	50	20
361-380	20	50	20
381-400	20	50	20
401-440	20	50	30
421-440	20	50	30
441-460	20	50	30
461-480	20	50	30
481-500	20	50	30
501-520	20	50	30
521-540	20	50	30
541-560	20	50	30
561-580	20	50	30
581-600	20	50	30
601-620	20	50	40
621-640	20	50	40
641-660	20	50	40
661-680	20	50	40
681-700	20	50	40

SGI	H	BI
From – 22.5 to 25	1	29.5-53
From – 22.5 to 25	2	29.75-53.5
From – 22.5 to 25	3	30.25-54
From – 22.5 to 25	4	30.75-54.5
From – 22.5 to 25	5	31.25-55
From – 22.5 to 25	6	31.75-55.5
From – 22.5 to 25	7	32.25-56
From – 22.5 to 25	8	32.75-56.5
From – 22.5 to 25	9	33.25-57
From – 22.5 to 25	10	33.75-57.5
From – 22.5 to 25	1	34.25-58
From – 22.5 to 25	2	34.75-58.5
From – 22.5 to 25	3	35.25-59
From – 22.5 to 25	4	35.75-59.5
From – 22.5 to 25	5	36.25-60
From – 22.5 to 25	6	36.75-60.5
From – 22.5 to 25	7	37.25-61
From – 22.5 to 25	8	37.75-61.5
From – 22.5 to 25	9	38.25-62
From – 22.5 to 25	10	38.75-62.5
From – 22.5 to 25	1	39.25-63
From – 22.5 to 25	2	39.75-63.5
From – 22.5 to 25	3	40.25-64
From – 22.5 to 25	4	40.75-64.5
From – 22.5 to 25	5	41.25-65
From – 22.5 to 25	6	41.75-65.5
From – 22.5 to 25	7	42.25-66
From – 22.5 to 25	8	42.75-66.5
From – 22.5 to 25	9	43.25-67
From – 22.5 to 25	10	43.75-67.5
From – 22.5 to 25	1	44.25-68
From – 22.5 to 25	2	44.75-68.5
From – 22.5 to 25	3	45.25-69
From – 22.5 to 25	4	45.75-69.5
From – 22.5 to 25	5	46.25-70

In case of disintegrated rock mass with gradient discontinuities where the strike of formation is perpendicular to excavation axis when excavation drives with dip direction, the BI was calculated between 39 and 67. According to blasting characterization as it is described on chapter 2.3, blasting is characterized as easy to very easy. In case of blocky rock mass with gradient discontinuities where the strike of formation is perpendicular to excavation axis when excavation drives with dip direction, the BI

was calculated between 44 and 72. According to blasting characterization as it is described on chapter 2.3, blasting is characterized as easy to very easy. In case of intact and massive mass with gradient discontinuities where the strike formation is perpendicular to excavation axis when excavation drives with dip direction, the BI was calculated between 59 and 87 and according to blasting characterization as it is described on chapter 2.3, blasting is characterized as very easy. All in all, according

Table 2b BI calculations for widely spaced discontinuities.

α/α	RMD	JPS	JPO	SGI	H	BI
701-720	20	50	40	From – 22.5 to 25	6	46.75-70.5
721-740	20	50	40	From – 22.5 to 25	7	47.25-71
741-760	20	50	40	From – 22.5 to 25	8	47.75-71.5
761-780	20	50	40	From – 22.5 to 25	9	48.25-72
781-800	20	50	40	From – 22.5 to 25	10	48.75-72.5
801-820	50	50	10	From – 22.5 to 25	1	44.25-68
821-840	50	50	10	From – 22.5 to 25	2	44.75-68.5
841-860	50	50	10	From – 22.5 to 25	3	45.25-69
861-880	50	50	10	From – 22.5 to 25	4	45.75-69.5
881-900	50	50	10	From – 22.5 to 25	5	46.25-70
901-920	50	50	10	From – 22.5 to 25	6	46.75-70.5
921-940	50	50	10	From – 22.5 to 25	7	47.25-71
941-960	50	50	10	From – 22.5 to 25	8	47.75-71.5
961-980	50	50	10	From – 22.5 to 25	9	48.25-72
981-1,000	50	50	10	From – 22.5 to 25	10	48.75-72.5
1,001-1,020	50	50	20	From – 22.5 to 25	1	49.25-73
1,021-1,040	50	50	20	From – 22.5 to 25	2	49.75-73.5
1,041-1,060	50	50	20	From – 22.5 to 25	3	50.25-74
1,061-1,080	50	50	20	From – 22.5 to 25	4	50.75-74.5
1,081-1,100	50	50	20	From – 22.5 to 25	5	51.25-75
1,101-1,120	50	50	20	From – 22.5 to 25	6	51.75-75.5
1,121-1,140	50	50	20	From – 22.5 to 25	7	52.25-76
1,141-1,160	50	50	20	From – 22.5 to 25	8	52.75-76.5
1,161-1,180	50	50	20	From – 22.5 to 25	9	53.25-77
1,181-1,200	50	50	20	From – 22.5 to 25	10	53.75-77.5
1,201-1,220	50	50	30	From – 22.5 to 25	1	54.25-78
1,221-1,240	50	50	30	From – 22.5 to 25	2	54.75-78.5
1,241-1,260	50	50	30	From – 22.5 to 25	3	55.25-79
1,261-1,280	50	50	30	From – 22.5 to 25	4	55.75-79.5
1,281-1,300	50	50	30	From – 22.5 to 25	5	56.25-80
1,301-1,320	50	50	30	From – 22.5 to 25	6	56.75-80.5
1,321-1,340	50	50	30	From – 22.5 to 25	7	57.25-81
1,341-1,360	50	50	30	From – 22.5 to 25	8	57.75-81.5
1,361-1,380	50	50	30	From – 22.5 to 25	9	58.25-82
1,381-1,400	50	50	30	From – 22.5 to 25	10	58.75-82.5
1,401-1,420	50	50	40	From – 22.5 to 25	1	59.25-83
1,421-1,440	50	50	40	From – 22.5 to 25	2	59.75-83.5
1,441-1,460	50	50	40	From – 22.5 to 25	3	60.25-84
1,461-1,480	50	50	40	From – 22.5 to 25	4	60.75-84.5
1,481-1,500	50	50	40	From – 22.5 to 25	5	61.25-85
1,501-1,520	50	50	40	From – 22.5 to 25	6	61.75-85.5
1,521-1,540	50	50	40	From – 22.5 to 25	7	62.25-86
1,541-1,560	50	50	40	From – 22.5 to 25	8	62.75-86.5
1,561-1,580	50	50	40	From – 22.5 to 25	9	63.25-87
1,581-1,600	50	50	40	From – 22.5 to 25	10	63.75-87.5

Table 3 RMR estimations for different types of rock mass with specific GSI range.

GSI (part)	A/A 1-80	A/A 81-140	A/A 141-200	A/A 201-280	A/A 281-340	A/A 341-400	A/A 401-480	A/A 481-540	A/A 541-600	A/A 601-680	A/A 681-740	A/A 741-800
	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR
I	14-54	21-62	29-62	009-54	16-62	24-62	0-42	14-62	19-42	17-59	14-38	32-67
J	16-56	23-64	31-64	0011-56	18-64	26-64	0-44	16-64	21-44	19-61	16-40	34-69
K	29-62	36-70	44-70	24-62	31-70	24-67	0012-50	29-70	27-58	32-67	39-75	47-75
L	33-68	40-76	48-76	28-68	35-76	28-73	16-56	33-76	31-64	36-73	33-62	51-81
M	37-70	44-78	52-78	32-70	39-78	32-75	20-58	38-78	35-66	40-75	37-69	55-83
N	018-59	25-67	33-67	13-59	20-67	28-67	001-47	18-67	23-55	21-64	18-43	36-72
O	20-61	27-69	35-69	15-61	22-69	30-69	003-49	20-69	25-57	23-66	20-45	38-74
P	30-67	37-75	45-75	25-67	32-75	40-75	13-55	30-75	28-63	41-75	30-66	48-80
Q	34-73	41-81	49-81	29-73	36-81	44-81	17-61	34-81	39-69	37-78	34-57	52-86
R	38-75	45-83	53-83	33-78	40-83	48-83	21-63	38-83	36-71	41-80	38-74	56-88
S	22-69	29-77	37-77	17-69	24-77	32-77	005-57	22-77	27-57	25-74	22-53	40-82
T	24-71	31-79	39-79	19-71	26-79	34-79	007-59	24-79	29-59	27-76	24-72	42-84
U	30-73	37-84	45-84	25-76	32-84	40-86	13-64	30-84	35-72	33-81	30-77	48-89
V	34-82	41-90	49-90	29-82	36-90	48-90	17-70	34-90	39-70	37-87	34-83	52-95
W	30-84	45-92	53-92	33-84	40-92	48-92	21-72	38-92	33-80	41-89	38-85	56-97
GSI (part)	A/A 801-880	A/A 881-940	A/A 941-1,000	A/A 1,001-1,080	A/A 1,081-1,140	A/A 1,141-1,200	A/A 1,201-1,280	A/A 1,281-1,340	A/A 1,341-1,400	A/A 1,401-1,480	A/A 1,481-1,540	A/A 1,541-1,600
	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR	RMR
X	46-77	53-87	61-87	41-79	48-87	56-87	39-79	41-75	54-87	49-84	56-92	64-92
Y	50-85	57-93	65-93	45-85	52-93	60-93	43-85	50-93	58-93	53-90	60-98	68-98
Z	54-87	61-95	69-95	49-87	56-95	64-95	47-87	54-100	62-95	57-92	64-100	72-100

Table 4 GSI estimations for different types of rock mass with specific RMR range.

RMR	A/A 1-80	A/A 81-140	A/A 141-200	A/A 201-280	A/A 281-340	A/A 341-400	A/A 401-480	A/A 481-540	A/A 541-600	A/A 601-680	A/A 681-740	A/A 741-800
	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)
0-20	IJN			IJNOST	IJN		IJKLMNOP QSTUV	IJNO	I	IJ	IJNO	
21-40	IJKLMNOP QRSTUVW	IJKLMNOPST U	IJNOST	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP STU	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP STUV	IJKLMNOP QRSTUVW	IJNO
41-60	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	IJKLMNOP KLMNOPQ RSTUVW	IJKLMNOP QRSTUVW
61-80	KLMOPQRS TUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	KLMOPQRS TUVW	IJKLMNOP QRSTUVW	IJKLMNOP QRSTUVW	QRUVW	IJKLMNOP QRSTUVW	LMPQRUV W	IJKLMNOP RSTUVW	KLMNPRTU VW	IJKLMNOP QRSTUVW
81-100	V	QRUVW	QRUVW	VW	QRUVW	QRUVW		QRUVW		UVW	VW	LMQRSTU VW

Table 5 GSI estimations for different types of rock mass with specific RMR range.

RMR	A/A 801-880	A/A 881-940	A/A 941-1,000	A/A 1,001-1,080	A/A 1,081-1,140	A/A 1,141-1,200	A/A 1,201-1,280	A/A 1,281-1,340
	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI (part)	GSI(part)	GSI(part)	GSI(part)
0-20	-	-	-	-	-	-	-	-
21-40	-	-	-	-	-	-	X	-
41-60	XYZ	XY	-	XYZ	XYZ	XY	XYZ	XYZ
61-80	XYZ	XYZ	XYZ	XYZ	XYZ	XYZ	XYZ	XYZ
81-100	YZ	XYZ	XYZ	YZ	XYZ	XYZ	YZ	XYZ

Table 6 GSI estimations for different types of rock mass with specific RMR range.

RMR	A/A 1,341-1,400	A/A 1,401-1,480	A/A 1,481-1,540	A/A 1,541-1,600
	GSI (part)	GSI (part)	GSI (part)	GSI (part)
0-20	-	-	-	-
21-40	-	-	-	-
41-60	XY	XYZ	XY	-
61-80	XYZ	XYZ	XYZ	XYZ
81-100	XYZ	XYZ	XYZ	XYZ

to the surface conditions and the structure of the rock mass, we can estimate GSI and RMR range. According to the estimated BI values, blasting is characterized of a relative easiness. A detailed evaluation of BI for every rock mass structure type is given on Fig. 2, so as the rock mass is classified according to GSI and RMR systems, the exact BI range may be estimated. According to the already known literature, the relation of BI and powder factor led to the conclusion, the optimal design and explosive parameters may safely be calculated.

3.2 BQS (Blastability Quality System)

BQS is a very useful approach as it includes the most useful characteristics of rock mass, which are easily estimated and used in situ. In addition to its easy and wide use, it is a quick calculator for the BI and rock mass quality, which make our choice of excavation, blast and support measures quicker.

The BI, calculated by Lilly, 1986, is used for the application of the dew diagram (BQS). This diagram consists of surfaces with specific range of BI, which depends on discontinuities characteristics. The calculated BI ranges are optimized according to the GSI or RMR estimations. So, The BQ system (Fig. 2) combines rock mass classification systems RMR and

GSI with structural data and the BI [17]. The long excavated and tunnelling practice establishes the strong relation of the classification systems RMR and GSI. Also, the estimations of RMR and GSI for every possible rock mass type support this opinion. The RMR and GSI results were combined so as they can be estimated graphically.

At the first stage, the orientation of discontinuities is distinguished. At the second stage, we can relate the structure to the surface conditions in order to estimate an area of RMR into diagrams. We can estimate the GSI using the gradient lines, too. Sometimes, we may use rock mass hardness (Mohs scale) [18] in order to estimate the exact area of GSI.

Having completed the above classification, the BI range can easily be determined at the left hand side of the diagram. Looking at rock structure, we can easily distinguish discontinuities in spacing and orientation [19]. At the final stage we can relate the structure to the surface conditions in order to estimate GSI and RMR.

Taking into consideration the GSI and RMR estimations, we can come up with appropriate excavation technique and support measures [4, 20, 21]. The ease of excavation, excavatability has been related with RMR and GSI (Saroglou & Tsiambaos) for the whole range of rock mass types. Although excavatability

Fig. 2 BQS (blastability quality system) for widely spaced discontinuities.

assessment includes also blasting ability, the already known literature does not estimate the BI at once. The ease of estimating the BI quickly is very useful in order to determine the required energy for fragmentation, the powder factor and explosive properties. Since the information required can be obtained from exploration drilling or from existing bench faces, it can be used in both the planning and production phases of projects requiring rock blasting. When coupled with computerized fragmentation models, the BI can provide an excellent means to experiment on the Visual Display Unit screen with a variety of blast designs, thereby avoiding expensive mistakes or miscalculations in the field.

4. In Situ Application of the Studied BQS Diagrams

Three in situ applications are analyzed. The use of BQS diagrams and the way of thinking during the applications are described. The first application is referred to tunneling excavation of ironed gneiss for Egnatia highway tunneling works in Northern Greece. The second and third applications are quarries which are used by TITAN Co. in Cyclades Islands in Aegean Sea.

4.1 First Application

The ironed gneiss consists of blocks which are formed by two main and one secondary discontinuity systems (Figs. 3 and 4). The main discontinuity systems are:

- i. Pegmatitic veins of horizontal discontinuities. Two discontinuities of the system are appeared on Fig. 3; downstairs and at the middle of the figure;
- ii. Inclined (about 45°) pegmatitic veins which cross the horizontal ones. One of the inclined pegmatitic veins is appeared at the left hand side of the Fig. 3.

A secondary discontinuity system is appeared at the right hand side of the Fig. 3. Some of those discontinuities are also appeared bottom of the figure. These discontinuities are closed and short and they are

cut by the discontinuities of the second main system. It is supposed that the secondary discontinuity system had been formed because of the explosion as the secondary discontinuity system is only appeared at right hand side of the rock mass.

Taking into consideration only the two main discontinuity systems, the rock mass structure is described as intact. But, the second discontinuity system must not be ignored at our estimations. So, our classification is more complete if the blocky structure of the rock mass will also be included. The discontinuities surface condition is rough, slightly weathered and ironed stained. Therefore, the surface condition is good.

So, the presence of two main discontinuity systems (the one with horizontal discontinuities and the other with inclined discontinuities with strike parallel to tunnel axis) lead us to separate two different areas; Area A and Area B (Fig. 4).

According to observation in situ, the estimations for Area A are:

GSI = 65-80, RMR = 41-80, BI = 55-65 (blasting is characterized as very easy);

The estimations for Area B are:

GSI = 60-80, RMR = 60-100, BI = 40-55 (blasting is characterized as very easy).

4.2 Second Application

The excavated formation consists by limestone with

Fig. 3 Ironed gneiss of first application.

Fig. 4 Example of classified areas on BQS.

Fig. 5 Limestone with three widely spaced major discontinuity systems.

Fig. 6 Bedding limestone.

three widely spaced major discontinuity systems (Fig. 5);

Vertical discontinuities; two discontinuities are appeared in Fig. 5; one of them is placed at the center of the figure and the other at the right. The discontinuity at the right side looks to be opened.

Closed discontinuities with rough surfaces, which are inclined less than 30° . One of the discontinuities is appeared in the center of the Fig. 5 and it extends to the left.

Closed discontinuities with rough surfaces, which are inclined about 45° and they cross the closed discontinuities which are inclined less than 30° . Three of them are appeared in Fig. 5; one at the left side of the figure, another at the right side, and a trace of another one at the center, near the cave. Infilled material is

appeared at the right side of the figure. But, the infilled material is not taking into account and is not described at classification, as it is rough and is completely incorporated in the formation.

According to the above in situ description, the classification is the same for the three discontinuities systems. Rock mass structure is intact or massive and the surface conditions are very good (very rough, fresh unweathered surfaces). Rock mass hardness, according to Mohs Scale, is 3. So, the classification of the rock mass is:

GSI = 80-100, RMR = 41-100, BI = 54-82 and the blasting is characterized as “very easy” (Fig. 4).

4.3 Third Application

The excavated formation is bedding limestone with three widely spaced discontinuity systems (Fig. 6):

i. Major discontinuity system which is parallel to bedding. The discontinuities are characterized by rough, slightly weathered surfaces. On the upper part of the Fig. 6.

ii. Secondary discontinuity system of inclined (about 45°) discontinuities with rough surfaces. Some of them are appeared on the center of the Fig. 6.

Looking the overall rock mass, although it consists of widely discontinuities, the structure fits with blocky-disturbed and seamy rock mass because of the bedding and the cross of the discontinuity systems.

Looking again the discontinuity systems, the two of them have the same orientation (strike parallel to excavation axis) and the one of them, which is parallel to bedding, is horizontal. So, we can separate two different classification's areas (Fig. 4):

Area A: it refers to horizontal discontinuities, which are parallel to beddings. The classification of the rock mass is: GSI = 30-40, RMR = 20-80, BI = 29-57 and the blasting is characterized as “easy to very easy”.

Area B: it refers to vertical discontinuities in addition to the secondary discontinuity system of inclined surfaces. As the hardness in Mohs Scale for calcite is 3, RMR is lower than 60. On the other hand

rock mass hardness is estimated from 5 to 7. According to the observation in situ, the classification of the rock mass is: $GSI = 40-50$, $RMR = 0-60$, $BI = 42-60$ and the blasting is characterized as “very easy”.

5. Conclusions

The present paper improves the effectiveness of the BQS for widely spaced discontinuities, combining the quality with blast ability of rock mass, which can be easily used in situ, for estimating, quickly, the explosion results, in relation to the excavation methods. All the possible combinations of rock mass geotechnical characteristics are used for the design of a diagram which combines rock mass quality with discontinuities orientation and rock mass hardness with BI. The emergent diagram refers to the “Blastability Quality System (BQS) for widely spaced discontinuities”. It can be used as a tool which combines rock mass quality with discontinuities orientation and rock mass hardness with the BI. It can be easily used during excavation process, in order to describe, quantitatively, the rock mass blasting and calculate the BI. This is a great help for deciding on explosions and support measures, in addition to the already known methods.

Three in situ examples of the new system and the way of thinking during the application of BQ-System are described in detail. The first application is referred to tunneling excavation of ironed gneiss for Egnatia highway tunneling works in Northern Greece. Two different areas are separated on diagram of BQ-System as there are two main discontinuity systems. As we try to interpret the results, we can observe that although the presence of the inclined discontinuities minimizes rock mass quality ($RMR = 41-80$) the GSI is about 60-80 and blasting is characterized as very easy ($BI = 40-65$).

The second and third applications are limestone quarries which are used by TITAN Co. in Cyclades Islands in Aegean Sea. The rock mass of the second application is very good, although there are locations where the quality is medium ($RMR = 41-100$). Taking

into account that GSI is high ($GSI = 80-100$), the above locations may not influence the excavation works so much. All in all, blasting is characterized as very easy ($BI = 54-82$).

The rock mass of the third application consists of bedding limestone. As there are three discontinuities sets with different characteristics, the rock mass quality varies from poor to good ($RMR = 0-80$), but the Geological Strength Index is about the same ($GSI = 30-50$). These geotechnical conditions do not change the ease of blasting so much as blasting is characterized “easy and very easy” ($BI = 30-60$).

On the above in situ examples, RMR and GSI in addition to BI are estimated using BQS, so as the engineers can form a collective opinion of rock mass behavior, and decide the most relevant excavation technique and support measures.

References

- [1] Chatziangelou, M., and Christaras, B. 2013. “Blastability Index on Poor Quality Rock Mass.” *Int. J. of Civil Engineering (IJCE)* 2 (5): 9-16.
- [2] Jimeno, C. L., Jinemo, E. L., and Carcedo, F. J. A. 1995. *Drilling & Blasting of Rock*. Rotterdam, Netherlands: Brookfield Publication, 160-80.
- [3] Palmstrom, Ar. 2000. “Recent Developments in Rock Support Estimates by the RMI.” *J Rock Mech. Tunnel Techn* 6 (1): 1-19.
- [4] Bieniawski, Z. T. 1989. *Engineering Rock Mass Classifications*. New York: Wiley.
- [5] Romana, M., Serón, J. B., and Montalar, E. 2003. “SMR Geomechanics Classification: Application, Experience and Validation.” In *ISRM 2003—Technology Roadmap for Rock Mechanics*. Johannesburg: South African Institute of Mining and Metallurgy.
- [6] Palmstrom, Ar. 2009. “Combining the RMR, Q and RMI Classification Systems.” *Tunnelling and Underground Space Technology* 24 (4): 491-2.
- [7] Hoek, E., Kaiser, P. K., and Bawden, W. F. 1995. *Support of Underground Excavations in Hard Rock*. Rotterdam, Netherlands: A.A. Balkema.
- [8] Hoek, E., and Karzulovic, A. 2000. “Rock Mass Properties for Surface Mines.” In *Slope Stability in Surface Mining*, edited by Hustralid, W. A., McCarter, M. K., and van Ayl, D. J. A. Littleton, Colorado: Society for Mining, Metallurgical and Exploration (SME), 59-70.
- [9] Mohs, F. 1812. *Versucheiner Elementar-Methode zur*

- Naturhistorischen Bestimmung und Erkennung von Fossilie.* Österreich Lexikon.
- [10] Palmström, A. 2005. "Measurements of and Correlations between Block Size and Rock Quality Designation (RQD)." *Tunnels and Underground Space Technology* 20: 362-77.
 - [11] Sonmez, H., and Ulusay, R. 1999. "Modifications to the Geological Strength Index (GSI) and Their Applicability to Stability of Slopes." *Int J Rock Mech Min Sci* 36: 743-60.
 - [12] Cai, M., Kaiser, P. K., Uno, H., Tasaka, Y., and Minami, M. 2004. "Estimation of Rock Mass Deformation Modulus and Strength of Jointed Hard Rock Masses Using the GSI System." *International Journal of Rock Mechanics and Mining Sciences* 41 (1): 3-19.
 - [13] Latham, J. P., and Ping, L. 1999. "Development of a Assessment System for the Blastability of Rock Masses." *International Journal of Rock Mechanics and Mining Sciences* 36: 41-55.
 - [14] Singh, P., and Sinha, Am. 2012. *Rock Fragmentation by Blasting*. Taylor & Francis, CRC Press.
 - [15] Kaushik, D., and Phalguni, S. 2003. "Concept of Blastability—An Update." *The Indian Mining & Engineering Journal* 42 (8 & 9): 24-31.
 - [16] Lilly, P. 1986. "An Empirical Method of Assessing Rock Mass Blastability." In *Proceedings of the Large Open Pit Mine Conference*, 89-92.
 - [17] Christaras, B., and Chatziangelou, M. 2014. "Blastability Quality System (BQS) for Using It, in Bedrock Excavation." *Structural Engineering and Mechanics, Techno-Press Ltd.* 51 (5): 823-45.
 - [18] Murthy, V., and Raitani, R. 2003. "Prediction of Overbreak in Underground Tunnel Blasting. A Case Study." *Journal of Canadian Tunneling Canadien*: 109-15.
 - [19] Priest, S. D., and Hudson, J. A. 1976. "Discontinuity Spacings in Rock." *Int. Jour. Rock. Mech. Min. Sci. & Gomech* 13: 135-48.
 - [20] Hino, K. 1959. *Theory and Practice of Blasting*. Noppon Kayaku Co, Ltd.
 - [21] Tsiambaos, G., and Saroglou, H. 2010. "Excavatability Assessment of Rock Masses Using the Geological Strength Index (GSI)." *Bull Eng Geol Environ* 69: 13-27.